

1Gbps Fibre Transmission

Single-Mode Bi-Directional Simplex SFP Transceiver

SIL-SFP0-01-25-B131-10XD


SIL-SFP0-01-25-B155-10XD

SIL-SFP0-01-25-B139-10XD

SIL-SFP0-01-25-B149-10XD

SIL-SFP0-01-25-B131-40XD

SIL-SFP0-01-25-B155-40XD



1Gbps Singlemode SFP

Bidirectional up to 40km

SIL-SFP0-01-25-B1XX-10XD

1Gbps Singlemode SFP

Bidirectional 10km

SFP0-01-25-B1XX-40XD

1Gbps Singlemode SFP

Bidirectional 40km

OVERVIEW

The SilverNet 1Gbps Singlemode BiDi (Bi Directional) SFP modules are ideal for use with Gigabit Ethernet switches and routers. They make extending Ethernet over distance easy using the Fibre ports on switches to daisy chain together.

The SilverNet SFP modules are capable of data rates up to 1Gbps over a distance of up to 40km. They are compliant with the SFP MSA specification and operate from 0~+70°C

Features

- Operating data rate up to 1.25Gbps
 - A type: 1310nm FP/DFB Laser Transmitter TX / 1550 or 1490nm RX
 - B type: 1550 or 1490nm FP/DFB Laser Transmitter TX / 1310nm RX
 - 10km and 40km with 9/125 μm SMF
 - Hot-Pluggable SFP Footprint Simplex LC Connector Interface
- Class 1 FDA and IEC60825-1 Laser Safety compliant
 - Digital Diagnostic Monitor Interface Compatible with SFF-8472
 - Single 3.3V power supply and TTL logic Interface
 - Compliant with SFP MSA specification
 - Operating temperature
 - Standard: 0~+70°C
 - Industrial: -40~+85°C

Part Code	Description
SIL-SFP0-01-25-B131-10XD	1G SM 1310nm TX FP 10km with DDM, 1550nm RX
SIL-SFP0-01-25-B155-10XD	1G SM 1550nm TX FP 10km with DDM, 1310nm RX
SIL-SFP0-01-25-B139-10XD	1G SM 1310nm TX FP 10km with DDM, 1490nm RX
SIL-SFP0-01-25-B149-10XD	1G SM 1490nm TX FP 10km with DDM, 1310nm RX
SIL-SFP0-01-25-B131-40XD	1G SM 1310nm TX DFB 40km with DDM, 1550nm RX
SIL-SFP0-01-25-B155-40XD	1G SM 1550nm TX DFB 40km with DDM, 1310nm RX

Copyright © SilverNet Limited. All rights reserved. All other company and product names may be trademarks of their respective companies. Whilst every effort is made to make sure the information shown is accurate, SilverNet Limited can not accept liability for any errors that may arise. No freedom to use information, patents, trademarks or other intellectual property rights is implied by the publication of this document. E&OE. SilverNet Limited reserve the right to change specifications and other information within this document without notice and your attention is brought to the fact that performance figures are under ideal conditions. Actual performance will depend on many environmental factors and it is recommended that a site survey is undertaken prior to installation. Please also note that this equipment may also be subject to local legislative restrictions. It is the end users responsibility to ensure that the installation complies with any such restrictions that are in force.



Distributed By: